



# DA-RL3W7

## 3" LED Recessed Downlight 7W

### Type IC & Airtight

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Trim Finish: \_\_\_\_\_ Qty: \_\_\_\_\_

Notes: \_\_\_\_\_



#### DESCRIPTION

Recessed 3" led downlight With Integral Driver In Connection Box.  
Fits Where No Other Recessed Fixture Can.

#### FEATURES & BENEFITS

- Install Directly Under Joists, Maximum Layout Flexibility
- Type IC Rated - No Housing Required
- Fast & Easy To Install - Save On Labour
- Driver Inside Connecton Box - No Junction Box Needed

#### MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips.  
2" Above Ceiling Clearance Required For Driver.  
Junction Box Dimensions (with driver inside): 110 mm x 82 mm x 32mm for 7w and 9W, 62\*60\*32mm for 5W

	SPECIFICATION
Applications	Recessed Ceiling Mount
Energy Used	2'' 5W ,3''7W, 4''9W
Colour Temperature	3000° K
Light Output	400lm,560lm,720lm
Halogen Equivalent	35-450 W
Beam Angle	60°
CRI	80
Driver Input	120V AC or 277V-347V AC 50/60 Hz
Power Factor	0.9
Dimming	TRIAC Dimmers 10% - 100% (120V only)
Approved Location	Insulated Ceiling & Damp Locations
Air Tight	Yes
Ambient Temperature	-40° F (-40° C) to +104° F (+40° C)
Projected Life	70% Light Output at 50,000 Hours
certification	CETL(5004879)
Warranty	5 Year on Fixture & Driver

